



TXMCO
同兴五金

泉州市同兴五金制品有限公司

自锁垫圈 SK5.S60C碳钢达克罗产品目录

Self-locking washer SK5.S60C carbon steel dacromet product catalog

序号	垫圈型号 Washer number	公制 Metric	内径 Øinner [mm]	外径 Øouter [mm]	厚度(对) Thk.(St) [mm]
	TX-5	M5	5.4±0.1	9±0.2	1.8±0.25
2	TX-6	M6	6.5±0.1	10.8±0.2	1.8±0.25
	TX-8	M8	8.7±0.1	13.5±0.2	2.5±0.25
4	TX-8D	M8	8.7±0.1	16.6±0.2	2.5±0.25
	TX-10	M10	10.7±0.2	16.6±0.2	2.5±0.25
6	TX-10D	M10	10.7±0.2	21.0±0.2	2.5±0.25
	TX-12	M12	13.1±0.2	19.5±0.2	2.5±0.25
8	TX-12D	M12	13.0±0.2	25.4±0.2	3.4±0.25
	TX-14	M14	15.2±0.2	23.0±0.2	3.4±0.25
10	TX-14D	M14	15.2±0.2	30.7±0.2	3.4±0.25
	TX-16	M16	17.0±0.2	25.4±0.2	3.4±0.25
12	TX-16D	M16	17.0±0.2	30.7±0.2	3.4±0.25
	TX-18	M18	19.5±0.2	29.0±0.2	3.4±0.25
14	TX-18D	M18	19.5±0.2	34.5±0.2	3.4±0.25
	TX-20	M20	21.4±0.2	30.7±0.2	3.4±0.25
16	TX-20D	M20	21.4±0.2	39.0±0.2	3.4±0.25
	TX-22	M22	23.4±0.2	34.5±0.2	3.4±0.25
18	TX-22D	M22	23.4±0.2	42.0±0.2	4.6±0.25
	TX-24	M24	26.5±0.5	39.0±0.2	3.4±0.25
20	TX-24D	M24	26.5±0.5	48.5±0.2	4.6±0.25
	TX-27	M27	30.0±0.5	42.0±0.3	5.8±0.25
22	TX-27D	M27	30.0±0.5	48.5±0.3	5.8±0.25
	TX-30	M30	33.0±0.2	47.0±0.3	5.8±0.25
24	TX-30D	M30	33.0±0.2	58.5±0.3	6.6-0.5
	TX-33	M33	36.0±0.2	48.5±0.3	5.8±0.25
26	TX-36	M36	39.5±0.2	55.0±0.3	5.8±0.25

技术要求:

1、硬度: ≥45HRC.

2、表面镀达克罗处理, 盐雾试验480小时。



自锁垫圈(钢结构用)SK5碳钢达克罗产品目录

Self-locking washer SK5 carbon steel dacromet product catalog

序号	垫圈型号 Washer number	公制 Metric	内径 øinner [mm]	倒角大径 øda [mm]	外径 øouter [mm]	厚度(对) Thk.(St) [mm]
	TX-24C	M24	25.3±0.2	26.4±0.2	39.0±0.2	3.4±0.25
2	TX-24DC	M24	25.3±0.2	26.4±0.2	48.5±0.2	4.6±0.25
	TX-27C	M27	28.4±0.2	30.4±0.2	42.0±0.3	5.8±0.25
4	TX-27DC	M27	28.4±0.2	30.4±0.2	48.5±0.3	5.8±0.25
	TX-30C	M30	31.4±0.2	33.4±0.2	47.0±0.3	5.8±0.25
6	TX-30DC	M30	31.4±0.2	33.4±0.2	58.5±0.3	6.6-0.5
	TX-33C	M33	34.4±0.2	36.4±0.2	48.5±0.3	5.8±0.25
8	TX-36C	M36	37.4±0.2	39.4±0.2	55.0±0.3	5.8±0.25
	TX-39C	M39	40.4±0.2	42.4±0.2	58.5±0.3	5.8±0.25
10	TX-42C	M42	43.2±0.2	45.6±0.2	63.0±0.3	5.8±0.25
	TX-45C	M45	46.2±0.5	48.6±0.3	70.0-2.0	7.0±0.75
12	TX-48C	M48	49.6±0.5	52.6±0.3	75.0-2.0	7.0±0.75
技术要求:						
1、硬度: ≥45HRC.						
2、表面镀达克罗处理, 盐雾试验480小时。						